

AMENDMENTS TO THE SPECIFICATION

The specification has been amended as follows:

Page 4

The heading before paragraph [0016] has been amended as follows:

DETAILED DESCRIPTION OF THE ~~PREFERRED EMBODIMENT~~ INVENTION

Paragraph [0016] on has been amended as follows:

[0016] The present invention will now be described in detail with reference to the accompanying drawings showing a ~~preferred embodiment~~ an embodiment thereof.

Pages 9-10

Paragraph [0027] has been amended as follows:

[0027] Therefore, even if the axis of the positioning projection 35 is deviated from the center of the positioning hole 42 in the directions of the height and width of the vehicle 1 when the lamp unit 3 is pressed into the lamp housing part 5 through the front opening thereof, the deviation is corrected when the positioning projection 35 is inserted into the positioning hole 42 as described above. Then, after the positioning ~~hole 34~~ surface 34 abuts on the flange 41 to completely fit the positioning projection 35 into the positioning hole 42, the positioning projection 35 never deviates from the center of the positioning hole 42 in the directions of the height and width of the vehicle 1. On this occasion, as the positioning projection 35 is inserted into the positioning hole 42, the positioning projection 35 increases in width, so that the positioning projection 35 can be tightly fitted

in the positioning hole 42 and prevented from being easily pulled out from the positioning hole 42.